

TRIDENT MK II : CRB



SPECIFICATIONS

	ų.	
Caliber:	5NI	6 mm
Overall Length:	222	675 mm (26.5") - 787 mm (31")
Overall Height:	avi V	223 mm (8.75")
Weight:	Ś	2.5 kg (5.5 lbs)
Outer Barrel Length:		266.7 mm (10.5")
Inner Barrel Length:		280 mm
Inner Barrel Diameter:		6.05 mm





VELOCITY (with 0.20g BB) Min: 365 FPS / 111 MPS Max: 385 FPS / 117 MPS

*Performance details are based on U.S. specifications and can be modified to meet the laws and regulations of your local region.

CHE OF	All specifications subject to change
EXTERNAL FEATURES	L L
KRYTAC MK II metal alloy	receivers
Licensed DEFIANCE® TR	110 keymod hand guard
Licensed DEFIANCE® pist	ol grip
KRYTAC battery stock	Ę
Ambidextrous fire selector	
Licensed CMC trigger	
MIL-STD 1913 Picatinny to	p rail
Ambidextrous sling loops	
Adjustable iron sights	
INTERNAL FEATURES	
8mm ball bearing mechbox	
Integrated FET system	······
Easy maintenance spring g	juide
Padded cylinder head	•••••••••••••••••••••••••••••••••••••••
Relief-cut cylinder window	•••••••
Anti-corrosion mechbox co	ating
Adjustable rotary hop-up	· · · · · · · · · · · · · · · · · · ·
Temperature and wear resi	stant hop-up bucking
KRYTAC 30K high torque r	notor
	·····