



TRIDENT MK II : PDW + SPR BUNDLE



SPECIFICATIONS

All specifications subject to change.

MK II SPR

Caliber:	6 mm
Overall Length:	863 mm (34") - 945 mm (37.25")
Overall Height:	223 mm (8.75")
Weight:	2.7 kg (5.9 lbs)
Outer Barrel Length:	406 mm (16")
Inner Barrel Length:	416 mm
Inner Barrel Diameter:	6.05 mm
Rate of Fire	20+ RPS
Velocity (with 0.20g BB)	Min: 400 FPS / 122 MPS Max: 420 FPS / 128 MPS

EXTERNAL FEATURES

- KRYTAC MK II metal alloy receivers
- Licensed DEFIANCE® TR113 keymod hand guard (SPR)
- Licensed DEFIANCE® TR105 keymod hand guard (PDW)
- Licensed DEFIANCE® pistol grip
- KRYTAC battery stock
- Ambidextrous fire selector
- Licensed CMC trigger
- MIL-STD 1913 Picatinny top rail
- Ambidextrous sling loops
- Adjustable iron sights

MK II PDW UPPER WITH KRTAC BATTERY STOCK

Caliber:	6 mm
Overall Length:	723.3 mm (28.5") - 805.3 mm (31.75")
Overall Height:	223 mm (8.75")
Weight:	2.4 kg (5.2 lbs)
Outer Barrel Length:	140 mm (5.5")
Inner Barrel Length:	155 mm
Inner Barrel Diameter:	6.05 mm
Rate of Fire	20+ RPS
Velocity (with 0.20g BB)	Min: 325 FPS / 99 MPS Max: 335 FPS / 102 MPS

INTERNAL FEATURES

- 8mm ball bearing mechbox
- Integrated FET system
- Easy maintenance spring guide
- Padded cylinder head
- Relief-cut cylinder window
- Anti-corrosion mechbox coating
- Adjustable rotary hop-up
- Temperature and wear resistant hop-up bucking
- KRYTAC 30K high torque motor

*Performance details are based on U.S. specifications and can be modified to meet the laws and regulations of your local region.