

TRIDENT MKII:PDW



SPECIFICATIONS

Caliber: 6 mm

Overall Length: 527 mm (20.75") - 610 mm (24")

Overall Height: 180 mm (7")

Weight: 2.27 kg (5 lbs)

Outer Barrel Length: 140 mm (5.5")

Inner Barrel Length: 155 mm

Inner Barrel Diameter: 6.05 mm

RATE OF FIRE 20+ RPS



VELOCITY (with 0.20g BB) Min: 325 FPS / 99 MPS Max: 335 FPS / 102 MPS

*Performance details are based on U.S. specifications and can be modified to meet the laws and regulations of your local region.

All specifications subject to change.

EXTERNAL FEATURES

KRYTAC MK II metal alloy receivers

Licensed DEFIANCE® TR105 keymod hand guard

Licensed DEFIANCE® pistol grip

Two-position compact carbine stock

Ambidextrous fire selector

Licensed CMC trigger

MIL-STD 1913 Picatinny top rail

Sling attachment loop

INTERNAL FEATURES

8mm ball bearing mechbox

Integrated FET system

Easy maintenance spring guide

Padded cylinder head

Relief-cut cylinder window

Anti-corrosion mechbox coating

Adjustable rotary hop-up

Temperature and wear resistant hop-up bucking

KRYTAC 30K high torque motor

SALES CONTACT T: +1 855 KRISS US (574-7787) F: +1 (714) 276-2740 E: SALES@KRYTAC.COM W: WWW.KRYTAC.COM