

TRIDENT MK II: SPR Foliage Green



SPECIFICATIONS

All specifications subject to change.

SIL	6 mm
750 750 750	863 mm (34") - 945 mm (37.25")
	223 mm (8.75")
5	2.7 kg (5.9 lbs)
า:	406 mm (16")
1:	416 mm
ter:	6.05 mm
	:

RATE OF FIRE 20+ RPS



VELOCITY (with 0.20g BB) Min: 400 FPS / 122 MPS Max: 420 FPS / 128 MPS

*Performance details are based on U.S. specifications and can be modified to meet the laws and regulations of your local region.

EXTERNAL FEATURES

KRYTAC MK II metal alloy receivers

Licensed DEFIANCE® TR113 keymod hand guard

Licensed DEFIANCE® pistol grip

KRYTAC battery stock

Ambidextrous fire selector

Licensed CMC trigger

MIL-STD 1913 Picatinny top rail

Ambidextrous sling loops

Adjustable iron sights

INTERNAL FEATURES

8mm ball bearing mechbox

Integrated FET system

Easy maintenance spring guide

Padded cylinder head

Relief-cut cylinder window

Anti-corrosion mechbox coating

Adjustable rotary hop-up

Temperature and wear resistant hop-up bucking

KRYTAC 30K high torque motor

SALES CONTACT T: +1 855 KRISS US (574-7787) F: +1 (714) 276-2740 E: SALES@KRYTAC.COM W: WWW.KRYTAC.COM