

# TRIDENT SDP



## SPECIFICATIONS

All specifications subject to change.

Caliber:	6 mm
Overall Length:	470 mm (18.5")
Overall Height:	180 mm (7")
Weight:	2.1 kg (4.1 lbs)
Outer Barrel Length:	140 mm (5.5")
Inner Barrel Length:	143 mm
Inner Barrel Diameter:	6.05 mm

### EXTERNAL FEATURES

- KRYTAC metal alloy receivers
- KRYTAC aluminum hand guard
- KRYTAC pistol buffer tube
- MIL-STD 1913 Picatinny top rail
- Ambidextrous fire selector
- Locking bolt and bolt release
- Sling attachment loop

### INTERNAL FEATURES

- 8mm ball bearing mechbox
- Integrated FET system
- Easy maintenance spring guide
- Padded cylinder head
- Relief-cut cylinder window
- Anti-corrosion mechbox coating
- Adjustable rotary hop-up
- Temperature and wear resistant hop-up bucking
- KRYTAC 30K high torque motor



**RATE OF FIRE**  
20+ RPS



**VELOCITY** (with 0.20g BB)  
Min: 315 FPS / 96 MPS  
Max: 325 FPS / 99 MPS

\*Performance details are based on U.S. specifications and can be modified to meet the laws and regulations of your local region.